

Data Structures and Algorithms

Lecture 07

Aniket Basu Roy

BITS Pilani Goa Campus

2026-01-27 Wed

Agenda

Quicksort

- ▶ Description
- ▶ Proof of Correctness
- ▶ Time Complexity

Quicksort

Input: $A[p : r]$

Divide

Conquer

Combine

Output: $A[p : r]$ is sorted.

Quicksort

Input: $A[p : r]$

Divide

Partition $A[p : r]$ into two (possibly empty) subarrays, $A[p : q - 1]$ and $A[q + 1 : r]$, such that $\forall a \in A[p : q - 1]$ and $\forall b \in A[q + 1 : r]$, $a \leq A[q] \leq b$.

Conquer

Recursively call QUICKSORT on the two subarrays, $A[p : q - 1]$ and $A[q + 1 : r]$.

Combine

Nothing to combine.

Output: $A[p : r]$ is sorted.

Quicksort

```
QUICKSORT( $A, p, r$ )
```

```
1  if  $p < r$ 
```

```
2      // Partition the subarray around the pivot, which ends up in  $A[q]$ .
```

```
3       $q = \text{PARTITION}(A, p, r)$ 
```

```
4      QUICKSORT( $A, p, q - 1$ ) // recursively sort the low side
```

```
5      QUICKSORT( $A, q + 1, r$ ) // recursively sort the high side
```

Merge Sort (Recall)

```
MERGE-SORT( $A, p, r$ )
1  if  $p \geq r$                                 // zero or one element?
2      return
3   $q = \lfloor (p + r) / 2 \rfloor$                     // midpoint of  $A[p : r]$ 
4  MERGE-SORT( $A, p, q$ )                          // recursively sort  $A[p : q]$ 
5  MERGE-SORT( $A, q + 1, r$ )                      // recursively sort  $A[q + 1 : r]$ 
6  // Merge  $A[p : q]$  and  $A[q + 1 : r]$  into  $A[p : r]$ .
7  MERGE( $A, p, q, r$ )
```

Quicksort

```
QUICKSORT( $A, p, r$ )
```

```
1  if  $p < r$ 
```

```
2      // Partition the subarray around the pivot, which ends up in  $A[q]$ .
```

```
3       $q = \text{PARTITION}(A, p, r)$ 
```

```
4      QUICKSORT( $A, p, q - 1$ ) // recursively sort the low side
```

```
5      QUICKSORT( $A, q + 1, r$ ) // recursively sort the high side
```

Quicksort

```
PARTITION( $A, p, r$ )
1   $x = A[r]$  // the pivot
2   $i = p - 1$  // highest index into the low side
3  for  $j = p$  to  $r - 1$  // process each element other than the pivot
4      if  $A[j] \leq x$  // does this element belong on the low side?
5           $i = i + 1$  // index of a new slot in the low side
6          exchange  $A[i]$  with  $A[j]$  // put this element there
7  exchange  $A[i + 1]$  with  $A[r]$  // pivot goes just to the right of the low side
8  return  $i + 1$  // new index of the pivot
```

Quicksort

Proof of Correctness

Quicksort

Proof of Correctness

- ▶ Correctness of the PARTITION function
 - ▶ Loop Invariant
- ▶ Proof by Induction on the number of array elements

Quicksort

Proof of Correctness

- ▶ Correctness of the PARTITION function
 - ▶ Loop Invariant

Quicksort

Proof of Correctness

- ▶ Correctness of the PARTITION function
 - ▶ Loop Invariant
 - ▶ Initialization
 - ▶ Maintenance
 - ▶ Termination

Quicksort

Time Complexity

Quicksort

Time Complexity

- ▶ (Un)balanced Partitions
 - ▶ Worst-case
 - ▶ Best-case
 - ▶ Balanced

Quicksort

Worst-case Time Complexity

$$T(n) = \max_{0 \leq q \leq n-1} (T(q) + T(n - q - 1)) + \Theta(n)$$